



TIGER-MATE™ 255

FIELD CULTIVATOR







RETHINK SEEDBED PRODUCTIVITY.

The Tiger-Mate 255 field cultivator creates a high-efficiency seedbed for the most accurate seed placement. This next-generation field cultivator series delivers agronomic advantages with each pass, helping you capitalize on your planter's ideal productivity levels to achieve maximum yield potential.

CASE IH AGRONOMIC DESIGN.

Agronomic Design™ means making the most of season, soil and seed. We know every individual plant counts toward your bottom line and that's why we design equipment that helps you maximize yield potential. From crop residue management to soil tilth to seedbed conditions, we designed the Tiger-Mate field cultivator with an eye on improving your agronomic performance.

Available on the Tiger-Mate 255 field cultivator, AFS Soil Command™ tillage technology allows producers to optimize the agronomic quality of their seedbed floor — right from the tractor cab. Advanced seedbed sensing technology allows you to sense hidden imperfections in your seedbed floor. Plus, with tillage prescriptions technology and total implement control, you can match variable tillage treatments to the specific conditions of your field like never before.

TIGER-MATE 255 FIELD CULTIVATOR

Agronomic Design	4
Welcome to High-Efficiency Farming	5
Here's How We Made the Industry's Leading Field Cultivator Better.	6-7
AFS Soil Command..	8-11
Where Force, Durability and Flexibility Meet	12-13
Creating the Optimal Seedbed	14-15
Designed to Keep You Rolling	16-17
Durability and Convenience Without Sacrifice	18-19
The Perfect Finish.	20-23
Specifications	25
Rethink Productivity	26-27

CREATING A POSITIVE ENVIRONMENT FOR AGRONOMIC PERFORMANCE.

The Tiger-Mate 255 field cultivator continues the Case IH tradition of superior tillage performance with its Agronomic Design features for ideal seedbed conditions. And now, with AFS Soil Command agronomic control technology, you have the tools to know what's hidden in your fields, so you can make agronomic adjustments.

CROP RESIDUE MANAGEMENT.

Built with Case IH Agronomic Design principles, the Tiger-Mate 255 features the combination of split-the-middle sweep pattern and 6.5 in. shank spacing that **provides maximum soil/residue mixing and distribution in all residue environments**. The results? Better soil tilth, healthy root development, and optimal soil and residue incorporation.

SOIL TILTH.

The swept-back, high-concavity shank design on the Tiger-Mate 255 helps soil ramp up and explode higher. This **breaks down tough clods and provides better residue mixing** and improves the incorporation of fertilizer and ag chemical applications.

SEEDBED CONDITIONS.

The ideal seedbed conditions are created by providing the desired soil levelness, flat floor, weed control and clod sizing for maximum seed-to-soil contact and stand emergence. The TigerMate 255 offers **increased ground speeds** (up to 10 mph) and the rugged shank spring force assembly **improves performance and flexibility in tough, fast-changing conditions**. This increase in shank holding power keeps the sweep parallel to the ground for a flatter subsurface floor and a smoother surface finish, creating a high-efficiency seedbed.



WELCOME TO HIGH-EFFICIENCY FARMING.

High-Efficiency Farming ensures seedbed preparation and seed placement accuracy are matched with the ideal speed for your individual field conditions and yield goals. It's not simply working faster. It's about finding the perfect match of tractor, tillage tool and planter to get the most from every field, every season.



Taking care of your seedbed is a **year-round job**. From crop residue distribution out the back of the combine to fall tillage to improving soil tilth, each step in the process leads you closer to the perfect seedbed.

LOOK DEEPER.

Seedbed conditions — a core principle of Case IH **Agronomic Design** — affect germination, plant development and, ultimately, yield potential. When you pull your planter through the gate, you expect a field that looks ready to plant — a field with a smooth, consistent soil surface. But the ideal seedbed reaches much deeper. What you can't see is as important as what you can see.

On the surface, the perfect seedbed is level, adequately firm and covered with small clods or a light mulch of crop residue to protect against soil erosion. Below ground, the **subsurface floor** where your planter places the seed

should be even more level, smooth and consistent than the field surface. In between, look for moisture throughout the seedbed depth. You also need soil that is well-mixed, providing the right soil-air-water balance and reliable incorporation. That's exactly what you get with the Tiger-Mate 255 field cultivator — a tillage tool that readies your fields faster and more efficiently than any tillage tool you've experienced.

START FAST, FINISH STRONG.

Fields that get off to a **quick, uniform** start yield better. When Iowa State University Extension specialists compiled and analyzed research from across the Midwest, they found that an uneven corn stand with just 17 percent of the plants emerging late yielded 4 percent to 8 percent less grain.¹ On 200-bushel-per-acre corn, that's 8 to 16 fewer bushels per acre. When lagging plants accounted for half the field, yields dropped by 20 percent.

The Iowa State specialists attribute late-emerging plants to several factors, including:

- Variation in soil temperature
- Seeding depth
- Crop residue distribution
- Soil crusting
- Soil moisture

Whether slicing and sizing the toughest crop residue, breaking through compaction or thoroughly mixing soil to improve soil tilth, the **full line** of Case IH tillage equipment can help you more precisely prepare each field according to your unique preferences. And then you can rely on the Tiger-Mate 255 to create the ideal seedbed and the 2000 series Early Riser® planter to perfectly place the seed into that environment.

¹Yield effect of uneven corn heights. Iowa State University Agronomy Extension website. <http://www.agronext.iastate.edu/corn/production/management/early/heights.html>. Accessed March 31, 2016.

HERE'S HOW WE MADE THE INDUSTRY'S LEADING FIELD CULTIVATOR BETTER.

Case IH Tiger-Mate field cultivators set the standard for seedbed preparation. The Tiger-Mate 255 builds on this legacy with several enhancements, plus added features and capabilities that help create a high-efficiency seedbed.

Equip double-fold units with a **wing wheel retraction feature** — standard on 37.4-, 40.6- and 46-foot models and optional for 51.5-, 55.8- and 60.1-foot versions — to reduce transport width by up to 13 inches.



The **split-the-middle sweep pattern** combined with a 6.5-inch shank spacing and 7.5-inch or 9-inch sweeps ensures 100 percent coverage for maximum crop residue mixing in the soil profile, along with thorough chemical incorporation.

See Page 15 for more information.



Greaseless bearings in the wing-wheel walking tandem beam, plus greaseless poly bushings in all wing and rockshaft pivots, **reduce maintenance for more uptime.**



Harrow options include a **3-bar, spike-tooth** Advanced Conditioning System (ACS) harrow paired with spring or hydraulic down pressure TigerPaw™ Crumbler®. Other options include: **3-bar Extreme Tiger-Tine** ACS with Spring or Hydraulic Down Pressure TigerPaw Crumbler, **2-bar Tiger-Tine** harrow with ACS roundbar Crumbler or a **4-bar Tiger-Tine** harrow. *See Page 21 for more information.*

The swept-back, **high-concavity shank** design helps soil explode higher, breaking tough clods and providing more consistent residue movement and better mixing.

■ The unique **bridge construction frame** is designed for strength and durability yet able to flex through the most difficult terrain.



■ A **single-point hydraulic depth control** is quick and easy to fine-tune depth to varying fields and conditions. Adjustments are holistic across the unit.



■ A **floating-hitch** option — available on double-fold units — allows the field cultivator to run independent of the tractor so it better follows the ground contour for improved depth consistency.

See Page 19 for more information.



The industry's first **stubble-resistant radial tires** feature reduced compaction, improved flotation and durability in the field and during transport.



■ The **improved shank assembly** balances the force and flexibility needed to produce a high-efficiency seedbed. The shank remains flexible to adjust to fast-changing conditions and keep sweeps parallel to the ground.

See Page 13 for more information.



UNLOCK YOUR SEEDBED'S AGRONOMIC POTENTIAL WITH **AFS SOIL COMMAND.**

In any field condition, AFS Soil Command tillage technology adds site-specific precision to soil management, unlocking more of a field's agronomic potential. The industry-leading Tiger-Mate 255 field cultivator creates an ideal seedbed, and AFS Soil Command helps operators further maximize their environmental, economic and agronomic performance with total implement control, as-tilled mapping and the ability to create and execute tillage prescriptions.



COORDINATED CONTROL.

AFS Soil Command agronomic control technology allows the operator to precisely coordinate control of every component of their Tiger-Mate 255 field cultivator to optimize all machine settings as field conditions change. With AFS Soil Command, when the shank depth is adjusted, all other functions of the machine — such as Crumbler pressure and stabilizer wheel position (constant-level only) — react to remain optimized for peak agronomic performance.

TILLAGE PRESCRIPTIONS.

Prescription technology takes the same variable rate approach you use for seed and fertilizer rates with site-specific tillage to create a high-efficiency seedbed. For example, when completing your final spring tillage pass with the Tiger-Mate 255 field cultivator, AFS Soil Command tillage prescriptions give producers the ability to adjust to properly incorporate fertilizer or chemicals, or run shallower to create a perfect seedbed for the planter.

ADD SITE-SPECIFIC PRECISION TO SOIL MANAGEMENT.

With AFS Soil Command tillage prescription technology, now you can tailor residue management, residue cover, surface compaction removal and clod sizing according to each field's varying conditions and agronomic needs.



SITE-SPECIFIC TILLAGE.

- From conservation to conventional, prescription technology takes the same variable rate approach you use for seed and fertilizer rates with site-specific tillage and zone management.
- Vary your practices based on changing soil types, field conditions and topography.
- Address a range of soil management challenges to make every inch of the field an optimal environment for plants, and minimize erosion and preserve moisture where needed.

SIMPLE OPERATION.


- Developed by the farm manager or an agronomist with the AFS Connect prescription creation tool, predetermined prescription maps indicate variable conditions as they occur, prompting automatic machine adjustments.
- With agronomic control technology, coordinated adjustments ensure the entire machine is set for peak performance — no matter the operator.
- Gather and visualize tillage data for better agronomic insights into your operation with AFS Connect.

PRODUCTIVE & EFFICIENT.

- Automatic adjustments are made quickly and efficiently as the operator travels across the field.
- Cover more acres by varying and increasing speed as conditions allow.
- Minimize equipment wear and tear — and maximize fuel efficiency — as the machine is adjusted in conditions that require little to no tillage treatment.

SEEDBED SENSING TECHNOLOGY FOR AN AGRONOMIC SEEDBED FLOOR.

Producers can measure and optimize the agronomic quality of their seedbed — right from the tractor cab — with AFS Soil Command seedbed sensing technology. It delivers real-time feedback from the seedbed to help the operator make yield-enhancing adjustments and eliminate the irregularities that lead to an uneven seedbed floor and planter row unit bounce.



MONITOR AGRONOMIC QUALITY.

- Built on Agronomic Design™ principles, AFS Soil Command helps producers fix seedbed issues before they become an issue for the planter.
- Sensors mounted to select shank assemblies on the Tiger-Mate 255 field cultivator alert the operator when the shanks begin to float, resulting in an uneven seedbed floor.
- The Advanced Farming Systems (AFS) Pro 700 display interface makes it easy for operators of any skill level to effectively monitor the Tiger-Mate 255 field cultivator.
- Green, yellow or red performance indicators are simple and easy to understand.

CREATE A HIGH-EFFICIENCY SEEDBED.

A high-efficiency seedbed is required for higher-efficiency planting and fast, uniform emergence. That means a seedbed that has a smooth surface finish and flat seedbed floor where the planter row unit can ride. Each time the field cultivator shank trips or floats, the sweep pivots, creating gouges in the seedbed floor that make the planter row unit bounce. AFS Soil Command provides a smooth, but not compacted, surface for the planter to ride on as it precisely places each seed.

RELIABLE SENSING TECHNOLOGY.

AFS Soil Command integrates reliable precision technology into each tillage pass. Factory-installed sensors are seamlessly integrated into the Tiger-Mate 255 to provide real-time, quality feedback to the operator on any ISOBUS-VT-compliant display. These sensors are built with dependable AFS components, matching the performance and ruggedness of the field cultivator. Operators can focus on creating an agronomic seedbed floor, instead of tending to their machine.



AGRONOMIC CONTROL TECHNOLOGY FOR THE PERFECT SEEDBED.

Proven and dependable AFS components integrated into the Tiger-Mate 255 field cultivator match the performance and ruggedness of Case IH tillage tools for increased durability, and in-cab controls for each system component allow operators to make every inch of the field an ideal crop environment.

OPTIMIZE EVERY PASS.

In-cab controls for each system component of the Tiger-Mate 255 field cultivator allow operators to make every inch of the field an ideal environment for plants.

- A properly set shank depth allows the Tiger-Mate to precisely condition the seedbed surface and seedbed floor to create the ideal environment for each seed.
- Fore and aft levelness delivers a consistent seedbed finish to complement seed placement during planting.
- Correct crumbler pressure settings allow for consistent clod sizing and finish.
- Up to four presets allow producers return to settings optimized for field conditions.



1 New hydraulic fore/aft control (Constant Level only): maintain consistent agronomic output



2 Shank depth: create an ideal seedbed surface and floor



3 Crumbler pressure: achieve consistent clod sizing and finish



4 Internally mounted sensing technology: precise control and feedback



5 Preset adjustments: maximize every acre



6 Coordinated control: optimize all tillage components



CREATING THE OPTIMAL SEEDBED — AT ALL LEVELS.

Every component of the field cultivator works in harmony to create a high-efficiency seedbed. Sweeps move soil. But it takes the right design, spacing and alignment to achieve success. Our Tiger-Mate series has earned a reputation for doing exactly that. It's widely recognized as one of the most agronomically sound field cultivators available.



Maxxi-Grip sweep, Maxxi-Point Plus sweep, and Maxxi-Point sweep.



A HIGH-EFFICIENCY PRODUCTIVITY BOOST.

The Tiger-Mate 255 features a more open design that allows today's higher crop residue levels to flow more easily and distribute more uniformly, regardless of speed. That means less plugging and a whole lot less operator frustration. We accomplished this productivity boost by **increasing the shank spacing** to 6.5 inches. That expands the minimum side-by-side shank spacing to 26 inches so residue flows more freely and mixes more completely.

DURABLE, LONG LASTING SWEEPS DELIVER MORE UPTIME.

Whether you choose to outfit your field cultivator with the **Maxxi-Point™**, **Maxxi-Grip™**, or **Maxxi-Point Plus™** sweep, you'll have peace of mind knowing that your sweeps' **Earth Metal®** alloy steel composition delivers increased toughness and longer wear life.

Earth Metal sweeps are made with special alloy steel and are heat-treated during manufacturing to prevent brittleness and loss of elasticity. This process allows Earth Metal sweeps to withstand the impact of hitting rocks or other obstacles in the field without bending or breaking. That means less time spent replacing broken or worn sweeps and more time preparing the ideal seedbed.

ADVANTAGES.

- Sweeps improve soil tilth and provide the proper pore and soil aggregate size and distribution.
- Complete, consistent coverage creates the ideal seedbed — from the surface to the subsurface floor.
- Combination of split-the-middle sweep pattern and 6.5-inch shank spacing provides maximum soil/residue mixing and distribution in all environments.
- High-strength Earth Metal sweeps for increased toughness and a longer life.




SPLIT-THE-MIDDLE DESIGN.


Our **split-the-middle sweep pattern** ensures 100 percent coverage for maximum crop residue mixing in the soil profile. This thoroughness also provides complete nutrient and chemical incorporation. With the 5-bar cut pattern, the sweeps in the first three rows take out a full cut. The last two rows take a smaller cut, removing the middles. As the sweep pattern turns every bit of soil, it promotes better soil tilth and healthy root development.

OPTIMAL SHANK SPACING, BETTER RESIDUE FLOW.


The **five-rank split-the-middle sweep pattern**, 6.5-inch shank spacing and 25 inches of underframe clearance provide space for greater residue flow with reduced plugging. It's an unbeatable combination that provides maximum soil and residue mixing and distribution and chemical incorporating in all residue environments. The first three ranks of sweeps are spaced farther apart than the rear two ranks. This helps flow more residue.



The standard V-pattern shank alignment causes uneven soil and residue flow and mixing and unbalanced sweep wear.



With the split-the-middle design, soil and crop residue flow equally around the sweeps for even, consistent soil and residue flow and mixing and a longer sweep lifespan.





DESIGNED TO KEEP YOU ROLLING.

High-efficiency seedbed preparation is about more than miles per hour. It's about less downtime and more uptime. Less time spent lubricating and adjusting. Fewer hours repairing and fighting plugs.



BUILT-IN LONGEVITY.

Welded bridge construction eliminates most butt-end welds and is **designed for strength and durability** yet able to flex through the most difficult terrain unlike competitive field cultivators that rely on 4-by-4-inch tubes and butt-end welds.

HIGHER CLEARANCE, HIGHER PRODUCTIVITY.

Today's hybrids produce more, tougher crop residue than ever. Building a stronger frame allowed us to provide **25 inches of underframe clearance** to keep residue flowing at higher speeds. That keeps you moving and helps make you more productive than ever.

AN INDUSTRY FIRST: RADIAL TIRES.

- Radial tires are standard and exclusive to the Tiger-Mate 255.
- Extremely reliable and stubble-resistant.
- Up to a 70 percent increase in footprint, compared with Bias Ply tires (9.5L×15).
- Improved flotation and reduced compaction.
- Durability pays off in the field and during transport.

DURABILITY AND CONVENIENCE WITHOUT SACRIFICE.

Our engineers tested and analyzed every component of the Tiger-Mate 255 frame against rigid standards. The result: Stronger construction, yet with the greater flexibility necessary to stand up to tough, fast-changing conditions.



EASY ADJUSTMENTS HELP MAINTAIN AN EVEN KEEL.

- Single-point hydraulic depth control lets you quickly and easily adjust for fast-changing conditions within a field or across your farm.
- Maintains equal depth across the entire field cultivator, including the wings.
- Tool-free turnbuckle provides easy leveling of the wings to the mainframe.
- A separate tool-free turnbuckle on units equipped with the constant-level hitch provides convenient fore and aft leveling to adjust to tractor hitch height.

BUILT-IN STABILITY.

- Walking tandems and gauge wheels on the main frame and wings provide a smooth ride and reduce compaction, wing bounce and nosing.
- Walking-tandem design offers balance and stability for a more consistent seedbed.
- Greaseless bushings on the wing wheel pivots increase uptime.
- Radial Stabilizer wheels on every wing section provide additional stability and levelness over obstacles.
- An available pivoting stabilizer wheel on wing sections is a good choice for contour farming. (Optional on constant-level hitch units)

REDUCED MAINTENANCE, INCREASED UPTIME.

- Durable construction and welded cylinders mean greater reliability.
- Greaseless bearings and bushings displace over 40 grease points on the double-fold unit and over 20 points on the single-fold models.
- Each displaced grease point saves about 1 minute in time to access and grease.
- Equates to 40 acres of productivity gained with the 60-foot model, assuming a ground speed that allows you to cover approximately 1 acre per minute.
- Remaining grease points require only annual grease intervals, so you spend your time in the field, rather than maintaining your Tiger-Mate field cultivator.



FLOATING HITCH ALLOWS BETTER FOLLOWING.

- Floating-hitch option, available on double-fold units, allows the Tiger-Mate 255 to operate independently of the tractor.
- Hitch pivots with the tractor over tough spots, but it lets the implement follow the ground for more consistently accurate depth across uneven terrain.
- T-bone hitch (on all models) allows for sharper, more efficient turning and a tighter turn radius.

WHICH HITCH DO I PICK?

- Floating hitch, best for:
 - Rougher, extreme rolling terrain
 - Waterways, ditches and terraces
 - Uneven ground
- Constant-level hitch, best for:
 - Relatively consistent rolling terrain
 - Level terrain

REAR HITCH AGRONOMIC CAPABILITIES.

- Rear hitch option accommodates an additional towed conditioning system.
- Enhances seedbed preparation without an added pass across the field.
- Capacity to tow a dual crumbler soil conditioning system.


THE PERFECT FINISH.

When it comes to tillage equipment, there may be no more personal choice than the finishing tool on the back of the unit. We let you pick the option that best provides the finish you desire. Select from our lineup of harrows to put the finishing touches on your seedbed.



2-BAR TIGER-TINE ACS HARROW WITH ROUND BAR CRUMBLER:

- Provides moderate clod sizing and seedbed firming.
- Indexed tines improve soil leveling.
- Parallel linkage and non-linked tine bars eliminate depth and level setting.
- Ideal for mellow or sandy loam soils found in prairie type soils.
- ACS 2-bar layout: 5 tines uniformly in contact with soil.
(measured from shank centerline)



3-BAR SPIKE-TOOTH ADVANCED CONDITIONING SYSTEM (ACS) HARROW WITH SPRING DOWN PRESSURE TIGERPAW CRUMBLER:

- ACS combination aggressively breaks up clods, evenly distributes crop residue and levels the soil for a smoother surface finish.
- Front rank of spikes are adjustable to match ground conditions.
- TigerPaw Crumbler features a formed bar for greater clod-busting power and excellent durability.
- Best choice for tough clods in forest soils prone to clodiness.



4-BAR TIGER-TINE HARROW:

- Three tine angle position adjustments.
- Indexed tines improve soil leveling.
- Parallel linkage and non-linked tine bars eliminate depth and level setting.


ADDITIONAL ADVANCED CONDITIONING SYSTEM HARROW OPTIONS.

Three additional Advanced Conditioning System (ACS) harrow options are available on the Tiger-Mate 255 that provide flexibility to match tough soil conditions. The additional tines on the Extreme Tiger-Time harrows provide more leveling and residue flow.



3-BAR EXTREME TIGER-TIME ACS HARROW WITH HYDRAULIC DOWN PRESSURE TIGERPAW CRUMBLER:

- Same great features as 3-bar Extreme Tiger-Time ACS harrow, but with hydraulic down pressure.
- The patented hydraulic down pressure system offers fast, easy, and independent adjustment of each section.
- The TigerPaw Crumbler may be placed in float or lifted on the go to avoid wet spots from the tractor cab.
- Ideal for prairie soils and heavy residue.
- ACS 3-bar layout: 10 tines uniformly in contact with soil.
(measured from shank centerline)



3-BAR EXTREME TIGER-TIME ACS HARROW WITH SPRING DOWN PRESSURE TIGERPAW CRUMBLER:

- 3-bar design and twice as many tines as the 2-bar ACS version, improves soil leveling.
- Extreme Tiger-Tines are redesigned for additional flexibility, allowing residue to filter through the tines yet keep maximum leveling.
- Four tine angle positions allow you to adjust soil smoothness to your preference adjustments.
- Large 14-inch Tiger-Paw Crumbler pulverizes the soil, reducing clod sizes.
- Ideal for prairie soils and heavy residue.

3-BAR SPIKE-TOOTH ACS HARROW WITH HYDRAULIC DOWN PRESSURE TIGERPAW CRUMBLER:

- Same great features as 3-bar spike-tooth ACS but with hydraulic down pressure.
- The patented hydraulic down pressure system offers fast, easy, and independent adjustment of each section.
- The TigerPaw Crumbler may be placed in float or lifted on the go to avoid wet spots from the tractor cab.
- Ideal for tough clods in forest soils prone to cloudiness.



Frame Type	Single Fold (Constant-Level Hitch)						Double Fold (Constant-Level Hitch)						Double Fold (Floating Hitch)							
Working Widths	22 ft. 2 in. (6.8 m)	25 ft. 6 in. (7.8 m)	28 ft. 8 in. (8.7 m)	32 ft. (9.8 m) Narrow Transport	32 ft. (9.8 m) Low Transport	35 ft. 2 in. (10.7 m)	37 ft. 5 in. (11.4 m)	40 ft. 7 in. (12.4 m)	46 ft. (14 m)	51 ft. 6 in. (15.7 m)	55 ft. 10 in. (17 m)	60 ft. 1 in. (18.3 m)	37 ft. 5 in. (11.4 m)	40 ft. 7 in. (12.4 m)	46 ft. (14 m)	51 ft. 6 in. (15.7 m)	55 ft. 10 in. (17 m)	60 ft. 1 in. (18.3 m)		
Main Frame Width	11.5 ft. (3.5 m)					13.5 ft. (4.1 m)	11.5 ft. (3.5 m)			13.5 ft. (4.1 m)			11.5 ft. (3.5 m)			13.5 ft. (4.1 m)				
Wing Size	6 ft. (1.8 m)		8 ft. (2.4 m)	10 ft. (3 m)	8 ft. (2.4 m)	10 ft. (3 m)	8 ft. (2.4 m)		10 ft. (3 m)		11 ft. (3.4 m)		8 ft. (2.4 m)		10 ft. (3 m)		11 ft. (3.4 m)			
Transport Width (At Outer Shank / At Wing Tandems When Folded)	14 ft. 11 in. (4.5 m) / N/A				17 ft. (5.2 m) / N/A		15 ft. 7 in. (4.8 m)			17 ft. 9 in. (5.4 m) / 19 ft. (5.8 m)		17 ft. 9 in. (5.4 m) / 18 ft. 7 in. (5.7 m)		15 ft. 7 in. (4.8 m)			17 ft. 9 in. (5.4 m) / 19 ft. (5.8 m)		17 ft. 9 in. (5.4 m) / 18 ft. 7 in. (5.7 m)	
Transport Width w/ Narrow Transport (Wing Wheel Retraction) Option	N/A						15 ft. 7 in. (4.8 m)			17 ft. 9 in. (5.4 m)			15 ft. 7 in. (4.8 m)			17 ft. 9 in. (5.4 m)				
Transport Height	10 ft. 2 in. (3.1 m)	11 ft. 1 in. (3.4 m)	12 ft. 6 in. (3.8 m)	14 ft. 2 in. (4.3 m)	12 ft. 6 in. (3.8 m)	14 ft. 2 in. (4.3 m)	12 ft. 3 in. (3.7 m)		13 ft. 5 in. (4.1 m)		15 ft. 6 in. (4.7 m)		12 ft. 3 in. (3.7 m)		13 ft. 5 in. (4.1 m)		15 ft. 6 in. (4.7 m)			
Length (w/o Harrow)	23 ft. 1 in. (7 m)						25 ft. 10 in. (7.86 m)			26 ft. (7.9 m)			29 ft. 8 in. (9 m)			29 ft. 11 in. (9.1 m)				
Max. Length (w/Harrow)	28 ft. 10 in. (8.78 m)						31 ft. 7 in. (9.6 m)			31 ft. 10 in. (9.7 m)			35 ft. 6 in. (10.9 m)			35 ft. 7 in. (10.9 m)				
Number of Shanks	41	47	53	59		65	69	75	85	95	103	111	69	75	85	95	103	111		
Weight	8,440 lb. (3828 kg)	8,700 lb. (3946 kg)	9,460 lb. (4291 kg)	9,920 lb. (4500 kg)		10,440 lb. (4736 kg)	15,725 lb. (7133 kg)	15,850 lb. (7189 kg)	17,400 lb. (7893 kg)	18,320 lb. (8310 kg)	19,750 lb. (8958 kg)	20,170 lb. (9149 kg)	17,950 lb. (8142 kg)	18,280 lb. (8292 kg)	19,010 lb. (8623 kg)	19,990 lb. (9067 kg)	21,460 lb. (9734 kg)	21,860 lb. (9916 kg)		
Drawbar Hitch Category	III				IV					V			IV			V				
Main Frame Tire Options	Standard: high-flotation 280/70R15 radial (Qty. 4) Optional: 9.5L-15 FI (Qty. 4) 6 bolt hubs						Standard: high-flotation 380/60R16.5 radial (Qty. 4) Optional: 12.5L-15 FI (Qty. 4) 8 bolt hubs			Standard: high-flotation 380/60R16.5 radial (Qty. 4) 8 bolt hubs			Standard: high-flotation 380/60R16.5 radial (Qty. 4) Optional: 12.5L-15 FI (Qty. 4) 8 bolt hubs			Standard: high-flotation 380/60R16.5 radial (Qty. 4) 8 bolt hubs				
Wing Tire Options	Standard: high-flotation 280/70R15 radial (Qty. 4) Optional: 9.5L-15 8-ply (Qty. 4) 6 bolt hubs						Standard: high-flotation 280/70R15 radial (Qty. 8) Optional: 9.5L-15 8-ply (Qty. 8) 6 bolt hubs						Standard: high-flotation 280/70R15 radial (Qty. 8) Optional: 9.5L-15 8-ply (Qty. 8) 6 bolt hubs							
Stabilizer Wheels	All wing sections: standard non-pivoting 5.90×15 (4-ply tubeless) tire size/optional: single-direction pivoting 7.60×15 (6 PR tubeless)						All wing sections: standard non-pivoting 5.90×15 (4-ply tubeless) tire size/optional: single-direction pivoting 7.60×15 (6 PR tubeless)						Main frame and all wing sections: standard castoring high-flotation - 280/80R15 radial/optional castoring 9.5L×15 FI (Main Frame), 8-ply (wings) tires							
Hitch System	Constant-level T-hitch with easy adjust front turnbuckle; swinging hose stand with operators manual storage												Floating T-hitch with easy adjust turnbuckle adjustment at each wing and mounted wrench on main frame; swinging hose stand with operators manual storage							
Wing Wheel Retraction (For Narrow Transport)	N/A						Standard			Optional			Standard			Optional				
SPECIFICATIONS																				
Main Frame	Bridge frame construction. Five ranks of 3×4 in. (76×102 mm) side-to-side and double 2×2 in. (51×51 mm) and 2×3 in. (51×76.2 mm) fore/aft structural members. Minimum rank spacing is 30 in. (762 mm) Total front to rear main bar is 131 in. (3 327 mm)																			
Shanks	Split-the-middle sweep pattern. 6.5 in. (165 mm) shank spacing. 11/16 in. × 1-3/4 in. (17.5×44.45 mm) shanks. Compression spring design with 180 lb. (68 kg) trip force and 14 in. (356 mm) trip height. Replaceable, double-hardened bushings used at shank pivot and spring slide area. Standard HD shank support channel																			
Sweeps	Standard: 7.5 in. (190.5 mm) Maxxi-Grip knock-on, optional: 7.3 in. (185.4 mm) long nose Maxxi-Point bolt-on, 7.3 in. (185.4 mm) Maxxi-Point Plus knock-on; 9 in. (228.6 mm) Maxxi-Grip knock-on, 9.3 in. (236.2 mm) long nose Maxxi-Point bolt-on																			
Depth Control System	Hydraulic single-point depth control. Maximum working depth 6 in. (152.4 mm); Optional AFS Soil Command control technology																			
Leveling System	Turnbuckle adjustment (no tools required); Optional hydraulic with AFS Soil Command control technology																			
Hydraulics	3,000 psi hydraulic welded cylinders, hoses and fittings. Male ISO couplers on hydraulic hoses to tractor; Optional AFS Soil Command — up to 3 remotes and power beyond required																			
Transport Lighting	ASABE standard LED warning and taillights with 7-pin connector. SMV emblem and reflectors. ASAE highway transport chain																			
Hubs and Spindles	Walking beam axles on both mainframe (greaseable) and wings (greaseless). Replaceable spindles on all walking beam axles																			
Horsepower Requirements	Varies with soil conditions and depth of tillage. 5-10 engine hp per foot or 2.5-5.5 engine hp per shank.																			
Recommended Operating Speeds	Recommended operating speed is 5.5 – 10 mph. ACS harrows only, Field conditions must be evaluated before operating above 8 mph.																			
Harrow Options	4-bar coil tine (16 in. Tiger-Tine) / ACS 3-bar spike with spring or hydraulic TigerPaw Crumbler [60–80 lb. per ft. (27.2– 36.3 kg per 0.3 m) down force] / ACS 2-bar Tiger-Tine with round bar rolling Crumbler [60–80 lb. per ft. (27.2– 36.3 kg per 0.3 m) down force] / 3-bar Extreme Tiger-Tine ACS harrow with spring or hydraulic TigerPaw Crumbler [60 – 80 lb. per ft. (27.2– 36.3 kg per 0.3 m) down force])																			

RETHINK PRODUCTIVITY.

When you consider all of the factors that go into raising a top-yielding crop, High-Efficiency Farming, simply put, means making the most of soil, seed and equipment to maximize yield potential.



HERE'S ONE EXAMPLE OF HOW CASE IH CAN HELP BRING TOGETHER THESE ELEMENTS ON YOUR FARM:

- Step 1** — Harvest: Even crop-residue distribution with your **Axial-Flow®** series combine
- Step 2** — Fall Tillage: Break up large clods with your **Ecolo-Tiger®** series disk ripper
- Step 3** — Spring Preparation: Create smooth, level seedbed with your **Tiger-Mate 255** field cultivator
- Step 4** — Plant: Accurately place seed with your **2000 series Early Riser** planter
- Step 5** — Feed and Protect: Precisely apply with your **Nutri-Placer** applicators and **Patriot®** series sprayers

Certainly, this describes a nearly ideal scenario — a year when the seasons and conditions break just right. But what happens when an early winter shuts down fall tillage? And that's followed by a wet spring? Or what happens when dry conditions slow residue breakdown? Or when different challenges conspire to squeeze your planting window? Today, as these types of years seem to trend more toward the norm than the exception, we're here to help.

When it comes to preparing the ideal seedbed, a final pass with the Case IH Tiger-Mate 255 field cultivator helps put your crops in the best position to achieve their **maximum yield potential**. Count on Case IH, our local dealer network and field personnel for the ideas and support you need to achieve your goals.





SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

Case IH, 621 State St., Racine, WI 53402, USA

©2021 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com

CIH21080402