

## **VESTRUM**<sup>™</sup>

SERIES TRACTOR





## **VESTRUM SERIES TRACTOR SPECIFICATIONS**

MODEL	VESTRUM 100 ACTIVEDRIVE 8 & CVXDRIVE™	VESTRUM 130 activedrive 8 & cyxdrive
Operator Station	Cab only	
Traction	MFD only	
ENGINE		
Туре	Tier 4 B/Final with 4 cylinder, turbocharged 4.5L FPT	
Displacement	273 cu. in.	
Engine HP*	100	130
PTO HP*	86	112
Emissions Treatment	Selective Catalytic Reduction (SCR)	
Number of Valves	16	
Alternator	200 amp	
Battery	12 volt - 176 Ah 1300 EN CCA	
TRANSMISSION/PTO		
Option (A)	24 x 24 ActiveDrive 8 dual-clutch transmission 25 MPH (40 KPH)	
Option (B)	CVXDrive CVT transmission 25 MPH (40 KPH)	
Creeper	Optional on ActiveDrive 8 transmission	
PTO	540/540E/1000 rpm Interchangable PTO shaft	
AXLES		
Front	Class 1.75 front axle with Electo hydraulic diff lock	
Rear	Flange	
HYDRAULICS/HITCH		
Туре	Closed center load sensing pump	
Rear Remotes (Standard/Optional)	2 Mechanical + 1 Electronic / 2 Mechanical + 2 Electronic	
Hydraulic Pump/Flow	28.5 gal./min. (108 L/min)	
3-Point Hitch Category (Standard/Optional)	EDC w/lower link sensing / Cat II flex link ends	
Standard Lift Capacity	6,700 lb. (3 039 kg) lift capacity with dual 80 mm external rams	
CAPACITIES		
Fuel Tank	47 gal. (180 L)	
Diesel Exhaust Fluid Tank	5 gal. (19 L)	
DIMENSIONS & WEIGHTS		
Wheelbase	98.1 in. (2 490 mm)	
Overall Length to End of Lower Links	188.6 in. (4 784 mm)	
Overall Height	111.70 in. (2 835 mm)	
Tractor Weight	12,900 lb.	

<sup>\*</sup> at 2,200 ERPM rated engine speed

SAFETY NEVER HURTS!<sup>TM</sup> Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

